REPORT DOCUMENTATION PAGE

Form Approved OMB No. 074-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing this collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503

4. TITLE AND SUBTITLE Numerical Optimization of Multifunctional Components 6. AUTHOR(S) Anthony T. Patera 7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Massachusetts Institute of Technology Dept. of Mechanical Engineering Room 3-266 77 Massachusetts Avenue Cambridge, MA 02139 9. SPONSORING/MONTORNING AGENCY NAME(S) AND ADDRESS(ES) Air Force Office of Scientific Research AFFORT NUMBER Alignon, VA 22203-1977 11. SUPPLEMENTARY NOTES 12a. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; Distribution unlimited. 13. ABSTRACT (Maximum 200 Works) Engineering components are increasingly complex in composition and structure and increasingly multifunctional: indeed, it is only through complexity and multifunctionality that we can satisfy the stringent performance requirements associated with critical defense applications. However, these complex, multifunctional systems no longer admit intuitive analysis of trade-off considerations: we must pursue optimization — optimal choice of material, configuration, and deployment — to realize the potential of these new approaches. The essential mathematical enabler — and our focus in this project — is very fast ye reliable prediction of component behavior; armed with the latter, we may then pursue extensive optimization and even real-time adaptive design and control. Critical ingredients of our approach are: (i) reduced-basis approximations to effect significant reduction in state-space dimensionality; (ii) a potentiar four provide rigorous error estimation and control, (iii) "Offline/online" computational decompositions to permit rapid evaluation of output bounds in the limit of many queries. In this project, we extend our basic methodology to non-coercive, non-affine, non-linear, and "non-elliptic" (parabolic) problems: we may thus now address the full range of disciplines that typically describe actual thermo-structure-fluid-acoustic-electromagnetic multifunctional compositions to potentit application, and control, (iii) "Offline/online" computation of	1. AGENCY USE ONLY (Leave blank)	2. REPORT DATE	3. REPORT TYPE AND DATES COVER		
Numerical Optimization of Multifunctional Components 6. AUTHOR(S) Anthony T. Patera 7. FERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Massachusetts Institute of Technology Dept. of Mechanical Engineering Room 3-266 77 Massachusetts Avenue Cambridge, MA. 02139 S. FUNSORING (MONITORING AGENCY NAME(S) AND ADDRESS(ES) Air Force Office of Scientific Research AFOSR/NM BOI North Randolph, Room 732 Arlington, VA. 22203-1977 11. SUPPLEMENTARY NOTES 12a. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; Distribution unlimited. 13. ABSTRACT (Maximum 200 Words) Engineering components are increasingly complex in composition and structure and increasingly multifunctional: indeed, it is only through complexity and multifunctionality that we can satisfy the stringent performance requirements associated with critical defense applications. However, these complex, multifunctional systems no longer admit intuitive analysis of trade-off considerations: we must pursue optimization — optimal choice of material, configuration, and deployment—to realize the potential frese new approaches. The essential mathematical enabler—and our focus in this project—is very fast yet reliable prediction of component behavior; armed with the latter, we may then pursue extensive optimization and even real-time adaptive design and control. Critical ingredients of our approach are: (i) reduced-basis approximations to effect significant reduction in state-space dimensionality; (ii) a pateriori error bounds to provide rigorous error estimation and control; (iii) "offline/online" computational decompositions to repermit rapid evaluation of output bounds in the limit of many paries. In this project, we extend our basic methodology to non-coercive, non-affine, non-linear, and "non-elliptic" (parabolic) problems: we may thus now address the full range of disciplines that typically describe actual thermo-structure-fluid-acoustic-electromagnetic multifunctional components.		August 17, 2004			
6. AUTHOR(S) Anthony T. Patera 7. FERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Massachusetts Institute of Technology Dept. of Mechanical Engineering Room 3-266 77 Massachusetts Avenue Cambridge, MA 02139 9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) Air Force Office of Scientific Research AFOSR/NM 801 North Randolph, Room 732 Arlington, VA 22203-1977 11. SUPPLEMENTARY NOTES 12a. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release; Distribution unlimited. 13. ABSTRACT (Maximum 200 World) Engineering components are increasingly complex in composition and structure and increasingly multifunctional: indeed, it is only through complexity and multifunctionality that we can satisfy the stringent performance requirements associated with critical defense applications. However, these complex, multimicroinal systems no longer admit intuitive analysis of trade-off considerations: we must pursue optimization — optimal choice of material, configuration, and deployment — to realize the potential of these new approaches. The essential mathematical enabler — and our focus in this project — is very fast yet reliable prediction of component behavior; armed with the latter, we may then pursue extensive optimization and even real-time adaptive design and control. Critical ingredients of our approach are: (i) reduced-basis approximations to effect significant reduction in state-space dimensionality; (ii) a pasteriori error bounds to provide rigorous error estimation and even real-time adaptive design and control. Critical ingredients of our approach are: (i) reduced-basis approximations to effect significant reduction in state-space dimensionality; (iii) a pasteriori error bounds to provide rigorous error estimation and even real-time adaptive design and control. Critical ingredients of our approach are: (i) reduced-basis approximations to effect significant reduction in state-space dimensionality; (iii) a pasteriori error bounds to provide rigorous error estimation and even real-time adaptive			5. FUNDING	NUMBERS	
7. FERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Massachusetts Institute of Technology Dept. of Mechanical Engineering Room 3-266 77 Massachusetts Avenue Cambridge, MA 02139 9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) Air Force Office of Scientific Research AFOSR/NM S01 North Randolph, Room 732 Arlington, VA 22203-1977 11. SUPPLEMENTARY NOTES 12a. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release; Distribution unlimited. 12b. DISTRIBUTION CODE 13. ABSTRACT (Maximum 200 Words) Engineering components are increasingly complex in composition and structure and increasingly multifunctional: indeed, it is only through complexity and multifunctionality that we can satisfy the stringent performance requirements associated with critical defense applications. However, these complex, multifunctional systems no longer admit intuitive analysis of trade-off considerations: we must pursue optimization — optimal choice of material, configuration, and deployment — to realize the potential of these new approaches. The essential mathematical enabler — and our focus in this project — is very fixely stret reliable periction of component behavior; armed with the latter, we may then pursue extensive optimization and even real-time adaptive design and control. Critical ingredients of our approaches are: (i) reduced-basis approximation sto effect significant reduction in state-space dimensionality; (ii) a posteriori error bounds to provide rigorous error estimation and control; (iii) "offline/online" computational decompositions to permit rapid evaluation of output bounds in the limit of many queries. In this project, we extend our basic methodology to non-coercive, non-affine, non-linear, and "non-elliptic" (parabolic) problems: we may thus now address the full range of disciplines that typically describe actual thermo-structure-fluid-acoustic-electromagnetic multifunctional components. 14. SUBJECT TERMS New Materials, Materials Concepts, Materials Processing and Devices: Structural and	Numerical Optimization of	Multifunctional Components	F49620-03-1	1-0356	
7. FERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Massachusetts Institute of Technology Dept. of Mechanical Engineering Room 3-266 77 Massachusetts Avenue Cambridge, MA 02139 9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) Air Force Office of Scientific Research AFOSR/NM S01 North Randolph, Room 732 Arlington, VA 22203-1977 11. SUPPLEMENTARY NOTES 12a. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release; Distribution unlimited. 12b. DISTRIBUTION CODE 13. ABSTRACT (Maximum 200 Words) Engineering components are increasingly complex in composition and structure and increasingly multifunctional: indeed, it is only through complexity and multifunctionality that we can satisfy the stringent performance requirements associated with critical defense applications. However, these complex, multifunctional systems no longer admit intuitive analysis of trade-off considerations: we must pursue optimization — optimal choice of material, configuration, and deployment — to realize the potential of these new approaches. The essential mathematical enabler — and our focus in this project — is very fixely stret reliable periction of component behavior; armed with the latter, we may then pursue extensive optimization and even real-time adaptive design and control. Critical ingredients of our approaches are: (i) reduced-basis approximation sto effect significant reduction in state-space dimensionality; (ii) a posteriori error bounds to provide rigorous error estimation and control; (iii) "offline/online" computational decompositions to permit rapid evaluation of output bounds in the limit of many queries. In this project, we extend our basic methodology to non-coercive, non-affine, non-linear, and "non-elliptic" (parabolic) problems: we may thus now address the full range of disciplines that typically describe actual thermo-structure-fluid-acoustic-electromagnetic multifunctional components. 14. SUBJECT TERMS New Materials, Materials Concepts, Materials Processing and Devices: Structural and					
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Massachusetts Institute of Technology Dept. of Mechanical Engineering Room 3-266 77 Massachusetts Avenue Cambridge, MA 02139 9. SPONSORING MONITORING AGENCY NAME(S) AND ADDRESS(ES) Air Force Office of Scientific Research AFOSR/NM 801 North Randolph, Room 732 Arlington, VA 22203-1977 11. SUPPLEMENTARY NOTES 12a. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release; Distribution unlimited. 13. ABSTRACT (Maximum 200 Words) Engineering components are increasingly complex in composition and structure and increasingly multifunctional: indeed, it is only through complexity and multifunctionality that we can satisfy the stringent performance requirements associated with critical defense applications. However, these complex, multifunctional systems no longer admit intuitive analysis of trade-off considerations: we must pursue optimization — optimal choice of material, configuration, and deployment — to realize the potential of these new approaches. The essential mathematical enabler — and our focus in this project — is very fast yet reliable prediction of component behavior, armed with the latter, we may then pursue extensive optimization and even real-time adaptive design and control. Critical ingredients of our approach are: (i) reduced-basis approximations to effect significant reduction in state-space dimensionality; (ii) a posteriori error bounds to provide rigorous error estimation and control; (iii) "offline/online" computational decompositions to permit rapid evaluation of output bounds in the limit of many queries. In this project, we extend our basic methodology to non-coercive, non-affine, non-linear, and "non-elliptic" (parabolic) problems: we may thus now address the full range of disciplines that typically describe actual thermo-structure-fluid-acoustic-electromagnetic multifunctional and Compositions to Perfect significant reduction and compositions to Perfect significant reduction in state-space dimensionality; (ii) a Posteriori error	6. AUTHOR(S)				
Massachusetts Institute of Technology Dept. of Mechanical Engineering Room 3-266 77 Massachusetts Avenue Cambridge, MA 02139 9. SPONSORING MONITORING AGENCY NAME(S) AND ADDRESS(ES) Air Force Office of Scientific Research AFOSR/NM 801 North Randolph, Room 732 Arlington, VA 22203-1977 11. SUPPLEMENTARY NOTES 12a. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release; Distribution unlimited. 13. ABSTRACT (Maximum 200 Words) Engineering components are increasingly complex in composition and structure and increasingly multifunctional: indeed, it is only through complexity and multifunctionality that we can satisfy the stringent performance requirements associated with critical defense applications. However, these complex, multifunctional systems no longer admit intuitive analysis of trade-off considerations: we must pursue optimization — optimal choice of material, configuration, and deployment — to realize the periotion of component behavior, armed with the latter, we may then pursue extensive optimization and even real-time adaptive design and control. Critical ingredients of our approach are: (i) reduced-basis approximation and control; (iii) "offline/online" computational decompositions to permit rapid evaluation of output bounds in the limit of many queries. In this project, we extend our basic methodology to non-coercive, non-affine, non-linear, and "non-elliptic" (parabolic) problems: we may thus now address the full range of disciplines that typically describe actual thermo-structure-fluid-acoustic-electromagnetic multifunctional components. 14. SUBJECT TERMS New Materials, Materials Concepts, Materials Processing and Devices: Structural and 9	Anthony T. Patera				
Massachusetts Institute of Technology Dept. of Mechanical Engineering Room 3-266 77 Massachusetts Avenue Cambridge, MA 02139 9. SFONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) Air Force Office of Scientific Research AFOSR/NM 801 North Randolph, Room 732 Arlington, VA 22203-1977 11. SUPPLEMENTARY NOTES 12a. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release; Distribution unlimited. 13. ABSTRACT (Maximum 200 Words) Engineering components are increasingly complex in composition and structure and increasingly multifunctional: indeed, it is only through complexity and multifunctionality that we can satisfy the stringent performance requirements associated with critical defense applications. However, these complex, multifunctional systems no longer admit intuitive analysis of trade-off considerations: we must pursue optimization — optimal choice of material, configuration, and deployment — to realize the potential of these new approaches. The essential mathematical enabler — and our focus in this project — is very fast yet reliable prediction of component behavior; armed with the latter, we may then pursue extensive optimization and even real-time adaptive design and control. Critical ingredients of our approach are: (i) reduced-basis approximations to effect significant reduction in state-space dimensionality; (ii) a posteriori error bounds to provide rigorous error estimation and control; (iii) "offline/online" computational decompositions to permit rapid evaluation of output bounds in the limit of many queries. In this project, we extend our basic methodology to non-coercive, non-affine, non-linear, and "non-elliptic" (parabolic) problems: we may thus now address the full range of disciplines that typically describe actual thermo-structure-fluid-acoustic-electromagnetic multifunctional components.	7. PERFORMING ORGANIZATION NA	ME(S) AND ADDRESS(ES)	1		
Dept. of Mechanical Engineering Room 3-266 77 Massachusetts Avenue Cambridge, MA 02139 9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) Air Force Office of Scientific Research AFOSR/NM 801 North Randolph, Room 732 Arlington, VA 22203-1977 11. SUPPLEMENTARY NOTES 12a. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; Distribution unlimited. 13. ABSTRACT (Maximum 200 Words) Engineering components are increasingly complex in composition and structure and increasingly multifunctional: indeed, it is only through complexity and multifunctionality that we can satisfy the stringent performance requirements associated with critical defense applications. However, these complex, multifunctional systems no longer admit intuitive analysis of trade-off considerations: we must pursue optimization — optimal choice of material, configuration, and deployment — to realize the potential of these new approaches. The essential mathematical enabler — and our focus in this project — is very fast yet reliable prediction of component behavior; armed with the latter, we may then pursue extensive optimization and even real-time adaptive design and control. Critical ingredients of our approach are: (i) reduced-basis approximations to effect significant reduction in state-space dimensionality; (ii) a posteriori error bounds to provide rigorous error estimation and control; (iii) "offline/online" computational decompositions to permit rapid evaluation of output bounds in the limit of many queries. In this project, we extend our basic methodology to non-coercive, non-affine, non-linear, and "non-elliptic" (parabolic) problems: we may thus now address the full range of disciplines that typically describe actual thermo-structure-fluid-acoustic-electromagnetic multifunctional components. 14. SUBJECT TERMS New Materials, Materials Concepts, Materials Processing and Devices: Structural and	Massachusetts Institute of Technology			JMBER	
Room 3-266 77 Massachusetts Avenue Cambridge, MA 02139 9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) Air Force Office of Scientific Research AFOSR/NM 801 North Randolph, Room 732 Arlington, VA 22203-1977 11. SUPPLEMENTARY NOTES 12a. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release; Distribution unlimited. 13. ABSTRACT (Maximum 200 Words) Engineering components are increasingly complex in composition and structure and increasingly multifunctional: indeed, it is only through complexity and multifunctionality that we can satisfy the stringent performance requirements associated with critical defense applications. However, these complex, multifunctional systems no longer admit intuitive analysis of trade-off considerations: we must pursue optimization — optimal choice of material, configuration, and deployment — to realize the potential of these new approaches. The essential mathematical enabler — and our focus in this project — is very fast yet reliable prediction of component behavior; armed with the latter, we may then pursue extensive optimization and even real-time adaptive design and control. Critical ingredients of our approach are: (i) reduced-basis approximations to effect significant reduction in state-space dimensionality; (ii) a posteriori error bounds to provide rigorous error estimation and control; (iii) "offline/online" computational decompositions to permit rapid evaluation of output bounds in the limit of many queries. In this project, we extend our basic methodology to non-coercive, non-affine, non-linear, and "non-elliptic" (parabolic) problems: we may thus now address the full range of disciplines that typically describe actual thermo-structure-fluid-acoustic-electromagnetic multifunctional components. 14. SUBJECT TERMS New Materials, Materials Concepts, Materials Processing and Devices: Structural and					
77 Massachusetts Avenue Cambridge, MA 02139 9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) Air Force Office of Scientific Research AFOSR/NM 801 North Randolph, Room 732 Arlington, VA 22203-1977 11. SUPPLEMENTARY NOTES 12a. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release; Distribution unlimited. 13. ABSTRACT (Maximum 200 Words) Engineering components are increasingly complex in composition and structure and increasingly multifunctional: indeed, it is only through complexity and multifunctionality that we can satisfy the stringent performance requirements associated with critical defense applications. However, these complex, multifunctional systems no longer admit intuitive analysis of trade-off considerations: we must pursue optimization — optimal choice of material, configuration, and deployment — to realize the potential of these new approaches. The essential mathematical enabler — and our focus in this project — is very fast yet reliable prediction of component behavior; armed with the latter, we may then pursue extensive optimization and even real-time adaptive design and control. Critical ingredients of our approach are: (i) reduced-basis approximations to effect significant reduction in state-space dimensionality; (ii) a posteriori error bounds to provide rigorous error estimation and control; (iii) "offline/online" computational decompositions to permit rapid evaluation of output bounds in the limit of many queries. In this project, we extend our basic methodology to non-coercive, non-affine, non-intena, and "non-elliptic" (grabobic) problems: we may thus now address the full range of disciplines that typically describe actual thermo-structure-fluid-acoustic-electromagnetic multifunctional components. 14. SUBJECT TERMS New Materials, Materials Concepts, Materials Processing and Devices: Structural and					
2. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) Air Force Office of Scientific Research AFOSR/NM 801 North Randolph, Room 732 Arlington, VA 22203-1977 11. SUPPLEMENTARY NOTES 12a. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release; Distribution unlimited. 13. ABSTRACT (Maximum 200 Words) Engineering components are increasingly complex in composition and structure and increasingly multifunctional: indeed, it is only through complexity and multifunctionality that we can satisfy the stringent performance requirements associated with critical defense applications. However, these complex, multifunctional systems no longer admit intuitive analysis of trade-off considerations: we must pursue optimization — optimal choice of material, configuration, and deployment — to realize the potential of these new approaches. The essential mathematical enabler — and our focus in this project — is very fast reliable prediction of component behavior; armed with the latter, we may then pursue extensive optimization and even real-time adaptive design and control. Critical ingredients of our approach are: (i) reduced-basis approximations to effect significant reduction in state-space dimensionality; (ii) a posteriori error bounds to provide rigorous error estimation and control; (iii) "offline/online" computational decompositions to permit rapid evaluation of output bounds in the limit of many queries. In this project, we extend our basic methodology to non-corerive, non-affine, non-injear, and "non-elliptic" (parabolic) problems: we may thus now address the full range of disciplines that typically describe actual thermo-structure-fluid-acoustic-electromagnetic multifunctional components. 14. SUBJECT TERMS New Materials, Materials Concepts, Materials Processing and Devices: Structural and 9	l .				
Air Force Office of Scientific Research AFOSR/NM 801 North Randolph, Room 732 Arlington, VA 22203-1977 11. SUPPLEMENTARY NOTES 12a. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; Distribution unlimited. 13. ABSTRACT (Maximum 200 Words) Engineering components are increasingly complex in composition and structure and increasingly multifunctional: indeed, it is only through complexity and multifunctionality that we can satisfy the stringent performance requirements associated with critical defense applications. However, these complex, multifunctional systems no longer admit intuitive analysis of trade-off considerations: we must pursue optimization — optimal choice of material, configuration, and deployment — to realize the potential of these new approaches. The essential mathematical enabler — and our focus in this project — is very fast yet reliable prediction of component behavior; armed with the latter, we may then pursue extensive optimization and even real-time adaptive design and control. Critical ingredients of our approach are: (i) reduced-basis approximations to effect significant reduction in state-space dimensionality; (ii) a posteriori error bounds to provide rigorous error estimation and control; (iii) "offline/online" computational decompositions to permit rapid evaluation of output bounds in the limit of many queries. In this project, we extend our basic methodology to non-coercive, non-affine, non-linear, and "non-elliptic" (parabolic) problems: we may thus now address the full range of disciplines that typically describe actual thermo-structure-fluid-acoustic-electromagnetic multifunctional components. 14. SUBJECT TERMS New Materials, Materials Concepts, Materials Processing and Devices: Structural and 9	Cambridge, MA 02139				
Air Force Office of Scientific Research AFOSR/NM 801 North Randolph, Room 732 Arlington, VA 22203-1977 11. SUPPLEMENTARY NOTES 12a. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; Distribution unlimited. 13. ABSTRACT (Maximum 200 Words) Engineering components are increasingly complex in composition and structure and increasingly multifunctional: indeed, it is only through complexity and multifunctionality that we can satisfy the stringent performance requirements associated with critical defense applications. However, these complex, multifunctional systems no longer admit intuitive analysis of trade-off considerations: we must pursue optimization — optimal choice of material, configuration, and deployment — to realize the potential of these new approaches. The essential mathematical enabler — and our focus in this project — is very fast yer reliable prediction of component behavior; armed with the latter, we may then pursue extensive optimization and even real-time adaptive design and control. Critical ingredients of our approach are: (i) reduced-basis approximations to effect significant reduction in state-space dimensionality; (ii) a posteriori error bounds to provide rigorous error estimation and control; (iii) "offline/online" computational decompositions to permit rapid evaluation of output bounds in the limit of many queries. In this project, we extend our basic methodology to non-coercive, non-affine, non-linear, and "non-elliptic" (parabolic) problems: we may thus now address the full range of disciplines that typically describe actual thermo-structure-fluid-acoustic-electromagnetic multifunctional components. 14. SUBJECT TERMS New Materials, Materials Concepts, Materials Processing and Devices: Structural and 9	9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) 10. SPONS				
AFOSR/NM 801 North Randolph, Room 732 Arlington, VA 22203-1977 11. SUPPLEMENTARY NOTES 12a. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release; Distribution unlimited. 13. ABSTRACT (Maximum 200 Words) Engineering components are increasingly complex in composition and structure and increasingly multifunctional: indeed, it is only through complexity and multifunctionality that we can satisfy the stringent performance requirements associated with critical defense applications. However, these complex, multifunctional systems no longer admit intuitive analysis of trade-off considerations: we must pursue optimization — optimal choice of material, configuration, and deployment — to realize the potential of these new approaches. The essential mathematical enabler — and our focus in this project — is very fast yet reliable prediction of component behavior; armed with the latter, we may then pursue extensive optimization and even real-time adaptive design and control. Critical ingredients of our approach are: (i) reduced-basis approximations to effect significant reduction in state-space dimensionality; (ii) a posteriori error bounds to provide rigorous error estimation and control; (iii) "offline/online" computational decompositions to permit rapid evaluation of output bounds in the limit of many queries. In this project, we extend our basic methodology to non-coercive, non-affine, non-linear, and "non-elliptic" (parabolic) problems: we may thus now address the full range of disciplines that typically describe actual thermo-structure-fluid-acoustic-electromagnetic multifunctional components. 14. SUBJECT TERMS New Materials, Materials Concepts, Materials Processing and Devices: Structural and 9	i l				
11. SUPPLEMENTARY NOTES 12a. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release; Distribution unlimited. 13. ABSTRACT (Maximum 200 Words) Engineering components are increasingly complex in composition and structure and increasingly multifunctional: indeed, it is only through complexity and multifunctionality that we can satisfy the stringent performance requirements associated with critical defense applications. However, these complex, multifunctional systems no longer admit intuitive analysis of trade-off considerations: we must pursue optimization — optimal choice of material, configuration, and deployment — to realize the potential of these new approaches. The essential mathematical enabler — and our focus in this project — is very fast yet reliable prediction of component behavior; armed with the latter, we may then pursue extensive optimization and even real-time adaptive design and control. Critical ingredients of our approach are: (i) reduced-basis approximations to effect significant reduction in state-space dimensionality; (ii) a posteriori error bounds to provide rigorous error estimation and control; (iii) "offline/online" computational decompositions to permit rapid evaluation of output bounds in the limit of many queries. In this project, we extend our basic methodology to non-coercive, non-affine, non-linear, and "non-elliptic" (parabolic) problems: we may thus now address the full range of disciplines that typically describe actual thermo-structure-fluid-acoustic-electromagnetic multifunctional components. 14. SUBJECT TERMS New Materials, Materials Concepts, Materials Processing and Devices: Structural and	l	arch	N/A		
11. SUPPLEMENTARY NOTES 12a. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release; Distribution unlimited. 13. ABSTRACT (Maximum 200 Words) Engineering components are increasingly complex in composition and structure and increasingly multifunctional: indeed, it is only through complexity and multifunctionality that we can satisfy the stringent performance requirements associated with critical defense applications. However, these complex, multifunctional systems no longer admit intuitive analysis of trade-off considerations: we must pursue optimization — optimal choice of material, configuration, and deployment — to realize the potential of these new approaches. The essential mathematical enabler — and our focus in this project — is very fast yet reliable prediction of component behavior; armed with the latter, we may then pursue extensive optimization and even real-time adaptive design and control. Critical ingredients of our approach are: (i) reduced-basis approximations to effect significant reduction in state-space dimensionality; (ii) a posteriori error bounds to provide rigorous error estimation and control; (iii) "offline/online" computational decompositions to permit rapid evaluation of output bounds in the limit of many queries. In this project, we extend our basic methodology to non-coercive, non-affine, non-linear, and "non-elliptic" (parabolic) problems: we may thus now address the full range of disciplines that typically describe actual thermo-structure-fluid-acoustic-electromagnetic multifunctional components. 14. SUBJECT TERMS New Materials, Materials Concepts, Materials Processing and Devices: Structural and 9					
12a. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release; Distribution unlimited. 13. ABSTRACT (Maximum 200 Words) Engineering components are increasingly complex in composition and structure and increasingly multifunctional: indeed, it is only through complexity and multifunctionality that we can satisfy the stringent performance requirements associated with critical defense applications. However, these complex, multifunctional systems no longer admit intuitive analysis of trade-off considerations: we must pursue optimization — optimal choice of material, configuration, and deployment—to realize the potential of these new approaches. The essential mathematical enabler — and our focus in this project — is very fast yet reliable prediction of component behavior; armed with the latter, we may then pursue extensive optimization and even real-time adaptive design and control. Critical ingredients of our approach are: (i) reduced-basis approximations to effect significant reduction in state-space dimensionality; (ii) a posteriori error bounds to provide rigorous error estimation and control; (iii) "offline/online" computational decompositions to permit rapid evaluation of output bounds in the limit of many queries. In this project, we extend our basic methodology to non-coercive, non-affine, non-linear, and "non-elliptic" (parabolic) problems: we may thus now address the full range of disciplines that typically describe actual thermo-structure-fluid-acoustic-electromagnetic multifunctional components. 14. SUBJECT TERMS New Materials, Materials Concepts, Materials Processing and Devices: Structural and 9					
Approved for public release; Distribution unlimited. 13. ABSTRACT (Maximum 200 Words) Engineering components are increasingly complex in composition and structure and increasingly multifunctional: indeed, it is only through complexity and multifunctionality that we can satisfy the stringent performance requirements associated with critical defense applications. However, these complex, multifunctional systems no longer admit intuitive analysis of trade-off considerations: we must pursue optimization — optimal choice of material, configuration, and deployment — to realize the potential of these new approaches. The essential mathematical enabler — and our focus in this project — is very fast yet reliable prediction of component behavior; armed with the latter, we may then pursue extensive optimization and even real-time adaptive design and control. Critical ingredients of our approach are: (i) reduced-basis approximations to effect significant reduction in state-space dimensionality; (ii) a posteriori error bounds to provide rigorous error estimation and control; (iii) "offline/online" computational decompositions to permit rapid evaluation of output bounds in the limit of many queries. In this project, we extend our basic methodology to non-coercive, non-affine, non-linear, and "non-elliptic" (parabolic) problems: we may thus now address the full range of disciplines that typically describe actual thermo-structure-fluid-acoustic-electromagnetic multifunctional components.	Arlington, VA 22203-1977				
Approved for public release; Distribution unlimited. 13. ABSTRACT (Maximum 200 Words) Engineering components are increasingly complex in composition and structure and increasingly multifunctional: indeed, it is only through complexity and multifunctionality that we can satisfy the stringent performance requirements associated with critical defense applications. However, these complex, multifunctional systems no longer admit intuitive analysis of trade-off considerations: we must pursue optimization — optimal choice of material, configuration, and deployment — to realize the potential of these new approaches. The essential mathematical enabler — and our focus in this project — is very fast yet reliable prediction of component behavior; armed with the latter, we may then pursue extensive optimization and even real-time adaptive design and control. Critical ingredients of our approach are: (i) reduced-basis approximations to effect significant reduction in state-space dimensionality; (ii) a posteriori error bounds to provide rigorous error estimation and control; (iii) "offline/online" computational decompositions to permit rapid evaluation of output bounds in the limit of many queries. In this project, we extend our basic methodology to non-coercive, non-affine, non-linear, and "non-elliptic" (parabolic) problems: we may thus now address the full range of disciplines that typically describe actual thermo-structure-fluid-acoustic-electromagnetic multifunctional components. 14. SUBJECT TERMS New Materials, Materials Concepts, Materials Processing and Devices: Structural and 9	11. SUPPLEMENTARY NOTES				
Approved for public release; Distribution unlimited. 13. ABSTRACT (Maximum 200 Words) Engineering components are increasingly complex in composition and structure and increasingly multifunctional: indeed, it is only through complexity and multifunctionality that we can satisfy the stringent performance requirements associated with critical defense applications. However, these complex, multifunctional systems no longer admit intuitive analysis of trade-off considerations: we must pursue optimization — optimal choice of material, configuration, and deployment — to realize the potential of these new approaches. The essential mathematical enabler — and our focus in this project — is very fast yet reliable prediction of component behavior; armed with the latter, we may then pursue extensive optimization and even real-time adaptive design and control. Critical ingredients of our approach are: (i) reduced-basis approximations to effect significant reduction in state-space dimensionality; (ii) a posteriori error bounds to provide rigorous error estimation and control; (iii) "offline/online" computational decompositions to permit rapid evaluation of output bounds in the limit of many queries. In this project, we extend our basic methodology to non-coercive, non-affine, non-linear, and "non-elliptic" (parabolic) problems: we may thus now address the full range of disciplines that typically describe actual thermo-structure-fluid-acoustic-electromagnetic multifunctional components. 14. SUBJECT TERMS New Materials, Materials Concepts, Materials Processing and Devices: Structural and 9					
Approved for public release; Distribution unlimited. 13. ABSTRACT (Maximum 200 Words) Engineering components are increasingly complex in composition and structure and increasingly multifunctional: indeed, it is only through complexity and multifunctionality that we can satisfy the stringent performance requirements associated with critical defense applications. However, these complex, multifunctional systems no longer admit intuitive analysis of trade-off considerations: we must pursue optimization — optimal choice of material, configuration, and deployment — to realize the potential of these new approaches. The essential mathematical enabler — and our focus in this project — is very fast yet reliable prediction of component behavior; armed with the latter, we may then pursue extensive optimization and even real-time adaptive design and control. Critical ingredients of our approach are: (i) reduced-basis approximations to effect significant reduction in state-space dimensionality; (ii) a posteriori error bounds to provide rigorous error estimation and control; (iii) "offline/online" computational decompositions to permit rapid evaluation of output bounds in the limit of many queries. In this project, we extend our basic methodology to non-coercive, non-affine, non-linear, and "non-elliptic" (parabolic) problems: we may thus now address the full range of disciplines that typically describe actual thermo-structure-fluid-acoustic-electromagnetic multifunctional components. 14. SUBJECT TERMS New Materials, Materials Concepts, Materials Processing and Devices: Structural and 9					
Approved for public release; Distribution unlimited. 13. ABSTRACT (Maximum 200 Words) Engineering components are increasingly complex in composition and structure and increasingly multifunctional: indeed, it is only through complexity and multifunctionality that we can satisfy the stringent performance requirements associated with critical defense applications. However, these complex, multifunctional systems no longer admit intuitive analysis of trade-off considerations: we must pursue optimization — optimal choice of material, configuration, and deployment — to realize the potential of these new approaches. The essential mathematical enabler — and our focus in this project — is very fast yet reliable prediction of component behavior; armed with the latter, we may then pursue extensive optimization and even real-time adaptive design and control. Critical ingredients of our approach are: (i) reduced-basis approximations to effect significant reduction in state-space dimensionality; (ii) a posteriori error bounds to provide rigorous error estimation and control; (iii) "offline/online" computational decompositions to permit rapid evaluation of output bounds in the limit of many queries. In this project, we extend our basic methodology to non-coercive, non-affine, non-linear, and "non-elliptic" (parabolic) problems: we may thus now address the full range of disciplines that typically describe actual thermo-structure-fluid-acoustic-electromagnetic multifunctional components. 14. SUBJECT TERMS New Materials, Materials Concepts, Materials Processing and Devices: Structural and 9	12a DISTRIBUTION / AVAILABILITY	STATEMENT		12b. DISTRIBUTION CODE	
Distribution unlimited. 13. ABSTRACT (Maximum 200 Words) Engineering components are increasingly complex in composition and structure and increasingly multifunctional: indeed, it is only through complexity and multifunctionality that we can satisfy the stringent performance requirements associated with critical defense applications. However, these complex, multifunctional systems no longer admit intuitive analysis of trade-off considerations: we must pursue optimization — optimal choice of material, configuration, and deployment — to realize the potential of these new approaches. The essential mathematical enabler — and our focus in this project — is very fast yet reliable prediction of component behavior; armed with the latter, we may then pursue extensive optimization and even real-time adaptive design and control. Critical ingredients of our approach are: (i) reduced-basis approximations to effect significant reduction in state-space dimensionality; (ii) a posteriori error bounds to provide rigorous error estimation and control; (iii) "offline/online" computational decompositions to permit rapid evaluation of output bounds in the limit of many queries. In this project, we extend our basic methodology to non-coercive, non-affine, non-linear, and "non-elliptic" (parabolic) problems: we may thus now address the full range of disciplines that typically describe actual thermo-structure-fluid-acoustic-electromagnetic multifunctional components. 14. SUBJECT TERMS New Materials, Materials Concepts, Materials Processing and Devices: Structural and 9		~			
Engineering components are increasingly complex in composition and structure and increasingly multifunctional: indeed, it is only through complexity and multifunctionality that we can satisfy the stringent performance requirements associated with critical defense applications. However, these complex, multifunctional systems no longer admit intuitive analysis of trade-off considerations: we must pursue optimization — optimal choice of material, configuration, and deployment — to realize the potential of these new approaches. The essential mathematical enabler — and our focus in this project — is very fast yet reliable prediction of component behavior; armed with the latter, we may then pursue extensive optimization and even real-time adaptive design and control. Critical ingredients of our approach are: (i) reduced-basis approximations to effect significant reduction in state-space dimensionality; (ii) a posteriori error bounds to provide rigorous error estimation and control; (iii) "offline/online" computational decompositions to permit rapid evaluation of output bounds in the limit of many queries. In this project, we extend our basic methodology to non-coercive, non-affine, non-linear, and "non-elliptic" (parabolic) problems: we may thus now address the full range of disciplines that typically describe actual thermo-structure-fluid-acoustic-electromagnetic multifunctional components. 14. SUBJECT TERMS New Materials, Materials Concepts, Materials Processing and Devices: Structural and 9	Approved for public release;				
Engineering components are increasingly complex in composition and structure and increasingly multifunctional: indeed, it is only through complexity and multifunctionality that we can satisfy the stringent performance requirements associated with critical defense applications. However, these complex, multifunctional systems no longer admit intuitive analysis of trade-off considerations: we must pursue optimization — optimal choice of material, configuration, and deployment — to realize the potential of these new approaches. The essential mathematical enabler — and our focus in this project — is very fast yet reliable prediction of component behavior; armed with the latter, we may then pursue extensive optimization and even real-time adaptive design and control. Critical ingredients of our approach are: (i) reduced-basis approximations to effect significant reduction in state-space dimensionality; (ii) a posteriori error bounds to provide rigorous error estimation and control; (iii) "offline/online" computational decompositions to permit rapid evaluation of output bounds in the limit of many queries. In this project, we extend our basic methodology to non-coercive, non-affine, non-linear, and "non-elliptic" (parabolic) problems: we may thus now address the full range of disciplines that typically describe actual thermo-structure-fluid-acoustic-electromagnetic multifunctional components. 14. SUBJECT TERMS New Materials, Materials Concepts, Materials Processing and Devices: Structural and	Distribution unlimited.				
Engineering components are increasingly complex in composition and structure and increasingly multifunctional: indeed, it is only through complexity and multifunctionality that we can satisfy the stringent performance requirements associated with critical defense applications. However, these complex, multifunctional systems no longer admit intuitive analysis of trade-off considerations: we must pursue optimization — optimal choice of material, configuration, and deployment — to realize the potential of these new approaches. The essential mathematical enabler — and our focus in this project — is very fast yet reliable prediction of component behavior; armed with the latter, we may then pursue extensive optimization and even real-time adaptive design and control. Critical ingredients of our approach are: (i) reduced-basis approximations to effect significant reduction in state-space dimensionality; (ii) a posteriori error bounds to provide rigorous error estimation and control; (iii) "offline/online" computational decompositions to permit rapid evaluation of output bounds in the limit of many queries. In this project, we extend our basic methodology to non-coercive, non-affine, non-linear, and "non-elliptic" (parabolic) problems: we may thus now address the full range of disciplines that typically describe actual thermo-structure-fluid-acoustic-electromagnetic multifunctional components. 14. SUBJECT TERMS New Materials, Materials Concepts, Materials Processing and Devices: Structural and					
through complexity and multifunctionality that we can satisfy the stringent performance requirements associated with critical defense applications. However, these complex, multifunctional systems no longer admit intuitive analysis of trade-off considerations: we must pursue optimization — optimal choice of material, configuration, and deployment — to realize the potential of these new approaches. The essential mathematical enabler — and our focus in this project — is very fast yet reliable prediction of component behavior; armed with the latter, we may then pursue extensive optimization and even real-time adaptive design and control. Critical ingredients of our approach are: (i) reduced-basis approximations to effect significant reduction in state-space dimensionality; (ii) a posteriori error bounds to provide rigorous error estimation and control; (iii) "offline/online" computational decompositions to permit rapid evaluation of output bounds in the limit of many queries. In this project, we extend our basic methodology to non-coercive, non-affine, non-linear, and "non-elliptic" (parabolic) problems: we may thus now address the full range of disciplines that typically describe actual thermo-structure-fluid-acoustic-electromagnetic multifunctional components. 14. SUBJECT TERMS New Materials, Materials Concepts, Materials Processing and Devices: Structural and 9	13. ABSTRACT (Maximum 200 Words)				
through complexity and multifunctionality that we can satisfy the stringent performance requirements associated with critical defense applications. However, these complex, multifunctional systems no longer admit intuitive analysis of trade-off considerations: we must pursue optimization — optimal choice of material, configuration, and deployment — to realize the potential of these new approaches. The essential mathematical enabler — and our focus in this project — is very fast yet reliable prediction of component behavior; armed with the latter, we may then pursue extensive optimization and even real-time adaptive design and control. Critical ingredients of our approach are: (i) reduced-basis approximations to effect significant reduction in state-space dimensionality; (ii) a posteriori error bounds to provide rigorous error estimation and control; (iii) "offline/online" computational decompositions to permit rapid evaluation of output bounds in the limit of many queries. In this project, we extend our basic methodology to non-coercive, non-affine, non-linear, and "non-elliptic" (parabolic) problems: we may thus now address the full range of disciplines that typically describe actual thermo-structure-fluid-acoustic-electromagnetic multifunctional components. 14. SUBJECT TERMS New Materials, Materials Concepts, Materials Processing and Devices: Structural and 9	To single and a second section of the second	singly complex in composition (and structure and increasingly multifur	ectional: indeed it is only	
applications. However, these complex, multifunctional systems no longer admit intuitive analysis of trade-off considerations: we must pursue optimization — optimal choice of material, configuration, and deployment — to realize the potential of these new approaches. The essential mathematical enabler — and our focus in this project — is very fast yet reliable prediction of component behavior; armed with the latter, we may then pursue extensive optimization and even real-time adaptive design and control. Critical ingredients of our approach are: (i) reduced-basis approximations to effect significant reduction in state-space dimensionality; (ii) a posteriori error bounds to provide rigorous error estimation and control; (iii) "offline/online" computational decompositions to permit rapid evaluation of output bounds in the limit of many queries. In this project, we extend our basic methodology to non-coercive, non-affine, non-linear, and "non-elliptic" (parabolic) problems: we may thus now address the full range of disciplines that typically describe actual thermo-structure-fluid-acoustic-electromagnetic multifunctional components. 14. SUBJECT TERMS New Materials, Materials Concepts, Materials Processing and Devices: Structural and 9	Engineering components are increas	angly complex in composition a	and structure and increasingly muturul	ociated with critical defense	
must pursue optimization — optimal choice of material, configuration, and deployment — to realize the potential of these new approaches. The essential mathematical enabler — and our focus in this project — is very fast yet reliable prediction of component behavior; armed with the latter, we may then pursue extensive optimization and even real-time adaptive design and control. Critical ingredients of our approach are: (i) reduced-basis approximations to effect significant reduction in state-space dimensionality; (ii) a posteriori error bounds to provide rigorous error estimation and control; (iii) "offline/online" computational decompositions to permit rapid evaluation of output bounds in the limit of many queries. In this project, we extend our basic methodology to non-coercive, non-affine, non-linear, and "non-elliptic" (parabolic) problems: we may thus now address the full range of disciplines that typically describe actual thermo-structure-fluid-acoustic-electromagnetic multifunctional components. 14. SUBJECT TERMS New Materials, Materials Concepts, Materials Processing and Devices: Structural and 9	and institute and the second	slav multifunctional systems no	longer admit intuitive analysis of trad	e-off considerations: we	
approaches. The essential mathematical enabler — and our focus in this project — is very fast yet reliable prediction of component behavior; armed with the latter, we may then pursue extensive optimization and even real-time adaptive design and control. Critical ingredients of our approach are: (i) reduced-basis approximations to effect significant reduction in state-space dimensionality; (ii) a posteriori error bounds to provide rigorous error estimation and control; (iii) "offline/online" computational decompositions to permit rapid evaluation of output bounds in the limit of many queries. In this project, we extend our basic methodology to non-coercive, non-affine, non-linear, and "non-elliptic" (parabolic) problems: we may thus now address the full range of disciplines that typically describe actual thermo-structure-fluid-acoustic-electromagnetic multifunctional components. 14. SUBJECT TERMS New Materials, Materials Concepts, Materials Processing and Devices: Structural and 9	applications. However, these comp	d choice of material configuration	ion and deployment — to realize the r	otential of these new	
behavior; armed with the latter, we may then pursue extensive optimization and even real-time adaptive design and control. Critical ingredients of our approach are: (i) reduced-basis approximations to effect significant reduction in state-space dimensionality; (ii) a posteriori error bounds to provide rigorous error estimation and control; (iii) "offline/online" computational decompositions to permit rapid evaluation of output bounds in the limit of many queries. In this project, we extend our basic methodology to non-coercive, non-affine, non-linear, and "non-elliptic" (parabolic) problems: we may thus now address the full range of disciplines that typically describe actual thermo-structure-fluid-acoustic-electromagnetic multifunctional components. 14. SUBJECT TERMS New Materials, Materials Concepts, Materials Processing and Devices: Structural and 9	approaches. The acceptial mathema	tical enabler — and our focus in	n this project — is very fast yet reliable	e prediction of component	
Critical ingredients of our approach are: (i) reduced-basis approximations to effect significant reduction in state-space dimensionality; (ii) a posteriori error bounds to provide rigorous error estimation and control; (iii) "offline/online" computational decompositions to permit rapid evaluation of output bounds in the limit of many queries. In this project, we extend our basic methodology to non-coercive, non-affine, non-linear, and "non-elliptic" (parabolic) problems: we may thus now address the full range of disciplines that typically describe actual thermo-structure-fluid-acoustic-electromagnetic multifunctional components. 14. SUBJECT TERMS New Materials, Materials Concepts, Materials Processing and Devices: Structural and 9	behavior: armed with the latter we i	may then pursue extensive ontit	mization and even real-time adaptive d	esign and control.	
(ii) a posteriori error bounds to provide rigorous error estimation and control; (iii) "offline/online" computational decompositions to permit rapid evaluation of output bounds in the limit of many queries. In this project, we extend our basic methodology to non-coercive, non-affine, non-linear, and "non-elliptic" (parabolic) problems: we may thus now address the full range of disciplines that typically describe actual thermo-structure-fluid-acoustic-electromagnetic multifunctional components. 14. SUBJECT TERMS New Materials, Materials Concepts, Materials Processing and Devices: Structural and 9	behavior, armed with the fatter, we i	may then pursue extensive optin	inzation and even fear time adaptive a	osign and common	
(ii) a posteriori error bounds to provide rigorous error estimation and control; (iii) "offline/online" computational decompositions to permit rapid evaluation of output bounds in the limit of many queries. In this project, we extend our basic methodology to non-coercive, non-affine, non-linear, and "non-elliptic" (parabolic) problems: we may thus now address the full range of disciplines that typically describe actual thermo-structure-fluid-acoustic-electromagnetic multifunctional components. 14. SUBJECT TERMS New Materials, Materials Concepts, Materials Processing and Devices: Structural and 9	Critical ingredients of our approach	are: (i) reduced-basis approxim	ations to effect significant reduction in	state-space dimensionality:	
permit rapid evaluation of output bounds in the limit of many queries. In this project, we extend our basic methodology to non-coercive, non-affine, non-linear, and "non-elliptic" (parabolic) problems: we may thus now address the full range of disciplines that typically describe actual thermo-structure-fluid-acoustic-electromagnetic multifunctional components. 14. SUBJECT TERMS New Materials, Materials Concepts, Materials Processing and Devices: Structural and 15. NUMBER OF PAGES	(ii) a posteriori error bounds to prov	vide rigorous error estimation ar	nd control; (iii) "offline/online" compu	tational decompositions to	
coercive, non-affine, non-linear, and "non-elliptic" (parabolic) problems: we may thus now address the full range of disciplines that typically describe actual thermo-structure-fluid-acoustic-electromagnetic multifunctional components. 14. SUBJECT TERMS New Materials, Materials Concepts, Materials Processing and Devices: Structural and 15. NUMBER OF PAGES 9	permit rapid evaluation of output bo	ounds in the limit of many querie	es. In this project, we extend our basic	methodology to non-	
typically describe actual thermo-structure-fluid-acoustic-electromagnetic multifunctional components. 14. SUBJECT TERMS New Materials, Materials Concepts, Materials Processing and Devices: Structural and 9	coercive, non-affine, non-linear, and	i "non-elliptic" (parabolic) prob	olems: we may thus now address the fu	ll range of disciplines that	
14. SUBJECT TERMS New Materials, Materials Concepts, Materials Processing and Devices: Structural and 15. NUMBER OF PAGES 9	typically describe actual thermo-stru	acture-fluid-acoustic-electromag	gnetic multifunctional components.		
New Materials, Materials Concepts, Materials Processing and Devices: Structural and 9		`	-		
New Materials, Materials Concepts, Materials Processing and Devices: Structural and 9					
New Materials, Materials Concepts, Materials Processing and Devices: Structural and 9	14 CUDIECT TEDIAC			15 NUMBED OF DACES	

NSN 7540-01-280-5500

OF REPORT

17. SECURITY CLASSIFICATION

Unclassified

BEST AVAILABLE COPY

18. SECURITY CLASSIFICATION

Unclassified

OF THIS PAGE

Standard Form 298 (Rev. 2-89) Prescribed by ANSI Std. Z39-18

20. LIMITATION OF ABSTRACT

SAR

20040927 028

BEST AVAILABLE COPY

19. SECURITY CLASSIFICATION

Unclassified

OF ABSTRACT

Principal Investigator: A.T. Patera F49620-03-1-0356

Numerical Optimization of Multifunctional Components

Grant Number F49620-03-1-0356

Anthony T. Patera
Department of Mechanical Engineering
Massachusetts Institute of Technology

Background

Engineering components are increasingly complex in composition and structure and increasingly multifunctional: indeed, it is only through complexity and multifunctionality that we can satisfy the stringent performance requirements associated with critical defense applications. However, these complex, multifunctional systems no longer admit intuitive analysis of trade-off considerations: we must pursue optimization — optimal choice of material, configuration, and deployment — to realize the potential of these new approaches.

The optimization, control, and characterization of an engineering component or system requires the prediction of certain "quantities of interest," or performance metrics, which we shall denote outputs — for example deflections, maximum stresses, maximum temperatures, heat transfer rates, flowrates, or lifts and drags. These outputs are typically expressed as functionals of field variables associated with a parametrized partial differential equation which describes the physical behavior of the component or system. The parameters, which we shall denote inputs, serve to identify a particular "configuration" of the component: these inputs may represent design or decision variables, such as geometry — for example in optimization studies; control variables, such as actuator power — for example in real-time applications; or characterization variables, such as physical properties — for example in inverse problems. We thus arrive at an implicit input-output relationship, the evaluation of which demands solution of the underlying partial differential equation.

Our goal is the development of computational methods that permit *rapid* and *reliable* evaluation of this partial-differential-equation-induced input-output relationship *in the limit of many queries*—that is, in the design, optimization, control, and characterization contexts. The "many query" limit has certainly received considerable attention. Our approach is based on the reduced-basis method, first introduced in the late 1970s for nonlinear structural analysis [1,2], and subsequently developed more broadly in the 1980s and 1990s [3–7]. The reduced-basis method recognizes that the field variable is not, in fact, some arbitrary member of the infinite-dimensional solution space associated with the partial differential equation; rather, it resides on a much lower-dimensional manifold induced by the parametric dependence.

The reduced-basis approach, as earlier articulated, is local in parameter space in both practice and theory. To wit, Lagrangian or Taylor approximation spaces for the low-dimensional manifold are typically defined relative to a particular parameter point: the associated *a priori*

convergence theory relies on asymptotic (implicit function theorem) arguments in sufficiently small neighborhoods; the computational improvements — relative to conventional (say) finite element approximation — are often quite modest [4]. Our work [8–12] differs from these earlier efforts in several important ways: first, we develop (in some cases, provably) global approximation spaces; second, we introduce rigorous a posteriori error estimators; and third, we exploit offline/online computational decompositions (see [7] for an earlier application of this strategy within the reduced-basis context). These three ingredients allow us to reliably decouple the generation and projection stages of reduced-basis approximation, thereby effecting computational economies of several orders of magnitude.

First, the error in the reduced-basis approximation typically vanishes exponentially as a function of N, the dimension of the reduced-basis space: sufficient accuracy can thus be obtained with only N = O(10) - O(100) degrees of freedom. Second, we can rigorously and sharply bound (a posteriori) the error in the reduced-basis approximation of the outputs of interest, thus permitting optimal truncation — selection of (close to) the smallest N for which the desired error tolerance can be achieved. Third, we can decompose the computational effort into two stages: an expensive (offline) stage performed once; and an inexpensive (online) stage performed many times. The operation count for the online stage — in which, given a new value of the input, we calculate the output and associated error bound — depends only on N (typically very small) and the parametric complexity of the operator. This very low marginal cost is critical in the optimization context.

Particular Achievements

Non-coercive Problems

In our earlier work, we treated primarily coercive operators; in particular, our earlier approaches did not permit rigorous a posteriori error estimation for non-coercive operators. We recently have developed [11] and subsequently refined [13; 14] procedures that now permit rigorous a posteriori error estimation for noncoercive problems — such as the Helmholtz equation (reduced-wave equation) that arises in acoustics, elastodynamics, and electromagnetics. The critical new ingredient is a lower bound for the inf-sup constant (singular value) that characterizes the stability of the operator — and hence controls the relationship between the dual norm of the residual and the error. Our (most efficient) approach is based on a piecewise-constant or piecewise-linear construction that exploits classical concavity properties of the inf-sup eigenproblem [14]. Examples of Helmholtz reduced-basis approximation and associated a posteriori error estimation — and application to inverse problems in elasticity — are given in [14].

Non-linear Problems

In our earlier work, we treated primarily linear operators; in particular, our earlier approaches [9] did not permit rigorous *a posteriori* error estimation for nonlinear problems (except in certain monotonic cases [11]). We have recently developed approaches — at present restricted to quadratic nonlinearities such as the incompressible Navier-Stokes equations describing fluid

flow (though see below) — that do indeed permit rigorous a posteriori output bounds. The foundation is the Brezzi-Rappaz-Raviart theory for analysis of variational approximations of nonlinear partial differential equations [15]. The key computational ingredients are efficient offline-online evaluation of the dual norm of the residual (similar to the procedure we developed earlier for linear problems); adaptation of the non-coercive inf-sup lower bound described above to the nonlinear case; and quantitative calculation of the relevant Sobolev embedding constants characterizing the nonlinearity. The method is described in detail in [14; 16], with application to natural convection in an enclosure (a problem relevant to materials processing).

Non-affine Problems

Until recently, we could only treat partial differential equations that are (i) affine in the parameter, and (ii) at most quadratically nonlinear in the state variable. Absent these assumptions, our offline-online decomposition breaks down. In fact, both of these restrictions can be addressed by a new "empirical interpolation" approach developed in collaboration with Professor Yvon Maday of University Paris VI [17]. In this approach, we replace general non-affine, nonlinear functions of the parameter, spatial coordinate, and state variable with collateral reduced-basis expansions. The critical ingredients of the approach are (i) good collateral reduced-basis samples and spaces, (ii) a stable and inexpensive online interpolation procedure by which to determine the collateral reduced-basis coefficients (as a function of the parameter), and (iii) effective a posteriori error bounds with which to quantify the effect of the newly introduced truncation. With these techniques we can now efficiently and reliably consider many new parameter variations (e.g., general shape optimization) as well as many new classes of nonlinear phenomenon (e.g., radiation heat transfer [18]). (We note however that, in general, we do lose some rigor in our a posteriori error bounds.)

Non-elliptic (Parabolic) Problems

We have recently extended our reduced-basis and *a posteriori* error estimation procedures to parabolic problems — for example, the heat (transient conduction) equation. The essential ingredient is the identification of a new (parameter, time) variable in which to develop the reduced-basis approximation. The approach entails several key innovations relative to the elliptic case both as regards approximation (e.g., impulse sampling procedures that permit general temporal forcing functions — as arise in optimal control) and *a posteriori* error estimation (adjoint techniques that provide bounds for the error in particular outputs of interest as *a function of time*). The methods are further described — and applied to a model "blast deflector" problem — in [14].

Adaptive Sampling

We have developed — in all the contexts above (including the temporal parabolic case) — efficient adaptive sampling procedures that permit us to construct (greedily) optimal samples that, in turn, yield rapidly convergent (and numerically stable) reduced-basis spaces. Given an initial parameter sample and associated approximation space, we can readily calculate — thanks to our fast error bounds — (an approximation to) both the maximum error over the parameter space and the location of the largest errors; this then serves to select the next points to be

included in the sample (and, ultimately, to terminate the approximation upon satisfaction of a given "worst-case" tolerance). These methods are, in essence, "POD-like" economization procedures [19] in which we need never form the vast majority of the snapshots.

User Interfaces

In the past [20] we have developed an extensive Web repository system to house online servers and an associated suite of (thin) clients by which to access these codes. In addition, in the current project, we have developed a simpler variant of this idea: MATLAB .m files which — for a particular partial differential equation, output(s), and input domain — (self-)contain the databases and online codes that, at the usual MATLAB command-line level, can then be invoked to provide the desired output and output error bound for any given input. In essence, we reduce Navier-Stokes to the computational (and user) complexity — and certainty — of "sin(x)." (We note that the development of the MATLAB .m file is time consuming, and is furthermore specific to each particular application; however, once in place, the response to the "end user" is quite literally real-time.) Examples of these MATLAB .m files are of course available to the sponsor upon request.

Optimization

The most common approach to the optimization of systems described by partial differential equations is to combine state-of-the-art optimization techniques — such as pattern search techniques, Sequential Linear/Quadratic Programming (SLP/SQP) approaches, or Newton Interior Point Methods (IPM) — with state-of-the-art partial differential equation discretization techniques — such as the finite element method. The best approaches (e.g., [21]) consider the optimization formulation and partial differential equation treatment in an integrated fashion. However, even these "best methods" remain quite expensive — a sufficiently accurate discretization may require hundreds of thousands of degrees of freedom — with computational times often measured in hours or even days. Further exacerbating the situation, realistic design exercises typically require many optimization cycles — corresponding to variations in the design, operation, and environment parameters that define the objectives and constraints. In the multifunctional context, these difficulties are even further amplified by the presence of a variety of different equations, objectives, and constraints that rarely admit any overarching simple structure.

An alternative approach to the optimization of systems described by partial differential equation is to replace the (say) finite element discretization with a much lower order description. This description may take the form of a model based primarily on physical reasoning or empirical constructions, or of a formal approximation directly derived from the underlying partial differential equations. A variety of frameworks (e.g., [22]) have been proposed for the incorporation of these low order descriptions into the design and optimization context. The main outstanding difficulty is the lack of rigorous, sharp, inexpensive error estimators for the outputs which appear in the optimization statement. Absent such a measure of fidelity, either the model truncation must be chosen (arbitrarily) conservatively — thus compromising efficiency; or the model truncation may be chosen overly optimistically — thus compromising convergence, optimality, and feasibility (with respect to the exact mathematical description).

Our approach —reduced-basis-based optimization — is of course of the low-order-approximation variety. However, in contrast to earlier work, we provide — and incorporate into the optimization framework — rigorous error bounds that ensure reliability. In particular, in our optimization procedure we can (i) restrict attention to regions of the design space in which the model is provably accurate (or, alternatively, request adaptive improvement of the approximation as demanded by the optimization and design process), (ii) assess and control the suboptimality induced by the output approximation in the optimization results, and (iii), most importantly, rigorously ensure feasibility of the optimizers with respect to the exact mathematical description. The latter is particularly critical in real-time applications — in order to guarantee "safe" operation without recourse to (non-real-time) fiducial calculations.

There are two main components to our approach: the reduced-basis approximation (and error bound) which replaces the classical finite element approximation; and the appropriate incorporation of this approximation into the optimization procedure. The former are manifested in the latter in two important ways: in model constraints that, based on our error estimators, restrict attention to regions of the design space in which the approximation may be trusted — trusted to provide good predictions, and to provide meaningful gradients and Hessians; and in performance constraints that, through our error estimators, ensure that all proposed optimizers are in fact feasible with respect to the *exact* (more precisely, a very high-order "truth" finite element approximation of the exact) solution of the partial differential equation.

We do identify certain recommendations regarding the optimization procedure, and we provide the associated computational foundations. First, we recommend, given the smoothness of our problems (and approximations), that higher order information should be exploited; we thus develop efficient techniques for calculating the gradients and Hessians of our reduced-basis outputs and associated error estimators. Second, we recommend that the optimization procedure provide (intermediate) iterates that are strictly input-feasible, since violation of our "design-fidelity" constraints can lead to rapid divergence. And third, we recommend that, given the nonconvex nature of our problems, the optimization procedure correctly avoid non-optimal stationary (saddle) points, and hence provide true (at least local) optimizers. An example that integrates all these components is described in [23].

References

- 1. B.O. Almroth, P. Stern, and F. A. Brogan, Automatic choice of global shape functions in structural analysis, AIAA Journal, 1978, 16:525–528.
- 2. A.K. Noor and J.M. Peters, Reduced Basis Technique for Nonlinear Analysis of Structures, AIAA Journal, 1980, 18(4):455–462.
- 3. J. P. Fink and W. C. Rheinboldt, On the Error Behavior of the Reduced Basis Technique for Nonlinear Finite Element Approximations, Z. Angew. Math. Mech., 1983, 63(11):21–28.
- 4. T.A. Porsching, Estimation of the Error in the Reduced Basis Method Solution of Nonlinear Equations, Mathematics of Computation, 1985, 45(172): 487–496.
- 5. J.S. Peterson, The Reduced Basis Method for Incompressible Viscous Flow Calculations, SIAM J. Sci. Stat. Comput., 1989, 10(4): 777–786.

- 6. W.C. Rheinboldt, On the Theory and Error Estimation of the Reduced Basis Method for Multi-Parameter Problems, Nonlinear Analysis, Theory, Methods and Applications, 1993, 21(11): 849–858.
- 7. E. Balmes, Parametric Families of Reduced Finite Element Models: Theory and Applications, Mechanical Systems and Signal Processing, 1996, 10(4): 381–394.
- 8. L. Machiels, Y. Maday, I. B. Oliveira, A.T. Patera, and D.V. Rovas, Output Bounds for Reduced-Basis Approximations of Symmetric Positive Definite Eigenvalue Problems, C. R. Acad. Sci. Paris, Série I, 2000, 331: 153–158.
- 9. C. Prud'homme, D. Rovas, K. Veroy, Y. Maday, A.T. Patera, and G. Turinici, Reliable Real-Time Solution of Parametrized Partial Differential Equations: Reduced-Basis Output Bound Methods, Journal of Fluids Engineering, 2002, 124(1):70–80.
- 10. Y. Maday, A.T. Patera, and G. Turinici, Global *A Priori* Convergence Theory for Reduced-Basis Approximation of Single-Parameter Symmetric Coercive Elliptic Partial Differential Equations, C. R. Acad. Sci. Paris, Série I, 2002, 335(3):289–294.
- 11. K. Veroy, C. Prud'homme, D.V. Rovas, and A.T. Patera, *A Posteriori* Error Bounds for Reduced-Basis Approximation of Parametrized Noncoercive and Nonlinear Elliptic Partial Differential Equations (AIAA Paper 2003-3847), Proceedings of the 16th AIAA Computational Fluid Dynamics Conference, 2003.
- 12. K. Veroy, C. Prud'homme, and A.T. Patera, Reduced-Basis approximation of the Viscous Burgers Equations: Rigorous *A Posteriori* Error Bounds, C.R.Acad. Sci. Paris, Séries I, 2003, 337(9):619–624.
- 13. N.C. Nguyen, K. Veroy, and A.T. Patera, Certified Real-Time Solution of Parametrized Partial Differential Equations, Handbook of Materials Modeling, Kluwer Academic Publishing, 2004, to appear.
- 14. M.A. Grepl, N.C. Nguyen, K. Veroy, A.T. Patera, and G.R. Liu, Certified Rapid Solution of Parametrized Partial Differential Equations for Real-Time Applications, Proceedings of the 2nd Sandia Workshop of PDE-Constrained Optimization: Towards Real-Time and On-Line PDE-Constrained Optimization. SIAM Computational Science and Engineering Book Series, 2004, submitted for consideration.
- 15. F. Brezzi, J. Rappaz, and P.A. Raviart, Finite Dimensional Approximation of Nonlinear Problems, Part I. Branches of Nonsingular Solutions, Numer. Math., 1980, 36:1–25.
- 16. K. Veroy and A.T. Patera, Certified Real-Time Solution of the Parametrized Steady Incompressible Navier-Stokes Equations; Rigorous, Reduced-Basis A Posteriori Error Bound. Special Issue of Int. J. Numer. Meth. Fluids Proceedings for 2004 ICFD Conference on Numerical Methods for Fluid Dynamics, 2004, submitted for consideration.
- 17. M. Barrault, Y. Maday, N.C. Nguyen, and A.T. Patera, An "Empirical Interpolation" Method: Application to Efficient Reduced-Basis Discretization of Partial Differential Equations, C. R. Acad. Sci. Paris, Série I, 2004, submitted for consideration.
- 18. Y. Solodukhov, Reduced-Basis Methods Applied to Locally Non-Affine Problems. Ph.D. Thesis, Massachusetts Institute of Technology, in progress.
- 19. L. Sirovich, Turbulence and the Dynamics of Coherent Structures, Part 1: Coherent Structures. Quarterly of Applied Mathematics, 1987, 45: 561–571.
- C. Prud'homme, D.V. Rovas, K. Veroy, and A.T. Patera, A Mathematical and Computational Framework for Reliable Real-Time Solution of Parametrized Partial Differential Equations, Mathematical Modeling and Numerical Analysis, 2002, 36(5):747–771.

Principal Investigator: A.T. Patera F49620-03-1-0356

- 21. G. Biros and O. Ghattas, A Lagrange-Newton-Krylov-Schur Method for PDE-Constrained Optimization, SIAG/OPT Views-and-News, 2000, 11(1).
- 22. N. Alexandrov and J.E. Dennis, Jr., Multilevel Algorithms for Nonlinear Optimization, in Optimal Design and Control, Progr. Systems Control Theory, 1995, 19:1–22.
- 23. I.B. Oliveira and A.T. Patera, Reduced-Basis Techniques for Rapid Reliable Optimization of Systems Described by Parametric Partial Differential Equations. Optimization and Engineering, 2003, submitted for consideration.

Personnel Supported

Anthony T. Patera (principal investigator) Martin A. Grepl Ivan B. Oliveira Christophe Prud'homme Shu Heng (George) Pau Karen Veroy Professor, MIT Cambridge, MA Graduate Student, MIT, Cambridge, MA Postdoc, MIT, Cambridge, MA Postdoc, MIT, Cambridge, MA Graduate Student, MIT, Cambridge, MA Postdoc, MIT, Cambridge, MA

Interactions

Other collaborators

Nguyen Ngoc Cuong (National University of Singapore and the Singapore-MIT Alliance) and Professor Liu Gui-Rong (National University of Singapore) have participated in the inverse-problem aspects of our studies. Many mathematical aspects of this work were developed in collaboration with Professor Yvon Maday (Paris-VI) and Maxime Barrault (Paris-VI).

Conferences

K. Veroy, 16th AIAA Computational Fluid Dynamics Conference, Orlando, FL, June 23–26, 2003.

A.T. Patera, Invited Lecturer, ICFD Conference on Numerical Methods for Fluid Dynamics, The University of Oxford, 29 March – 1 April 2004.

A.T. Patera, Invited Speaker, Second Sandia Workshop on PDE-Constrained Optimization: Toward Real-time and Online PDE-constrained Optimization, May 19–21, 2004, Santa Fe, NM.

M.A. Grepl, 6th International Conference on Spectral and High Order Methods (ICOSAHOM 2004), Minisymposium — Reduced Basis Methods: New Trends, June 21–25, 2004, Brown University, Providence, RI

K. Veroy, 6th International Conference on Spectral and High Order Methods (ICOSAHOM 2004), Minisymposium — Reduced Basis Methods: New Trends, June 21–25, 2004, Brown University, Providence, RI

Publications

- 1. K. Veroy, C. Prud'homme, D.V. Rovas, and A.T. Patera, *A Posteriori* Error Bounds for Reduced-Basis Approximation of Parametrized Noncoercive and Nonlinear Elliptic Partial Differential Equations (AIAA Paper 2003-3847), Proceedings of the 16th AIAA Computational Fluid Dynamics Conference, 2003.
- 2. K. Veroy, C. Prud'homme, and A.T. Patera, Reduced-Basis approximation of the Viscous Burgers Equations: Rigorous *A Posteriori* Error Bounds, C.R. Acad. Sci. Paris, Séries I, 2003, 337(9):619–624.
- 3. N.C. Nguyen, K. Veroy, and A.T. Patera, Certified Real-Time Solution of Parametrized Partial Differential Equations, Handbook of Materials Modeling, Kluwer Academic Publishing, 2004, to appear.
- 4. M.A. Grepl, N.C. Nguyen, K. Veroy, A.T. Patera, and G.R. Liu, Certified Rapid Solution of Parametrized Partial Differential Equations for Real-Time Applications, Proceedings of the 2nd Sandia Workshop of PDE-Constrained Optimization: Towards Real-Time and On-Line PDE-Constrained Optimization. SIAM Computational Science and Engineering Book Series, 2004, submitted for consideration.
- K. Veroy and A.T. Patera, Certified Real-Time Solution of the Parametrized Steady Incompressible Navier-Stokes Equations; Rigorous, Reduced-Basis A Posteriori Error Bound. Special Issue of Int. J. Numer. Meth. Fluids — Proceedings for 2004 ICFD Conference on Numerical Methods for Fluid Dynamics, 2004, submitted for consideration.
- 6. M. Barrault, Y. Maday, N.C. Nguyen, and A.T. Patera, An "Empirical Interpolation" Method: Application to Efficient Reduced-Basis Discretization of Partial Differential Equations, C. R. Acad. Sci. Paris, Série I, 2004, submitted for consideration.
- 7. I.B. Oliveira and A.T. Patera, Reduced-Basis Techniques for Rapid Reliable Optimization of Systems Described by Parametric Partial Differential Equations. Optimization and Engineering, 2003, submitted for consideration.